Supplier:

Magnaloy Coupling Company 601 Palm Street / P.O. Box 455 Alpena MI 49707 (517) 356-2186 For Additional Information contact: Chardon Rubber Company 373 Washington Street Chardon OH 44024 440 285-2161

## SECTION I - PRODUCT IDENTIFICATION

CHEMICAL NAME: Chloroprene Rubber, 80 Durometer
TRADE NAME: Neoprene Rubber, 80 Durometer

FORMULA: CAS NO:

PHYSICAL FORM: Solid

\_\_\_\_\_

## SECTION II - COMPOSITION

\_\_\_\_\_

MATERIAL	Exposure Limits	%	PERMISSIBLE AIR LEVEL
Disproportionated Tall Oil		0.96	OSHA Title 29 CFR 1910.1200
Disproportionated Rosin		0.96	OSHA Title 29 CFR 1910.1200
Carbon Black	3.5mg/m <sup>3</sup>	54.72	OSHA Title 29 CFR 1910.1200
Extract, Distillate, Heavy Paraffinic		8.76	OSHA Title 29 CFR 1910.1200
N-Cyclohexyl-2-Benzothiazole Sulfenamide		0.41	OSHA Title 29 CFR 1910.1200
Zinc Oxide		0.96	SARA Title III
Polyethylene / Synthetic Calcium Silicate		2.05	OSHA Title 29 CFR 1910.1200
Magnesium Oxide		0.82	OSHA Title 29 CFR 1910.1200

\_\_\_\_\_\_

## SECTION III - PHYSICAL DATA

\_\_\_\_\_\_

SPECIFIC GRAVITY: 1.33 VAPOR PRESSURE: N/A

APPEARANCE AND ODOR: Rubber Solid with Rubber Smell

SOLUBILITY IN WATER: Insoluble

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A FLAMMABLE LIMITS: LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: Water

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CONTROL MEASURES: Practice good personal hygiene and wear cloth gloves and goggles when working with material.